

MAK Fastener Specialists Pty Ltd.,
Unit 4, 11 Trevi Crescent,
Tullamarine, VIC 3043
Australia.

Web Site: www.makfasteners.com.au

Tel.: +61 (0)3 9078 9119

Fax: +61 (0)3 9078 9119

E-mail: Sales@MakFasteners.com.au



MAK
FASTENER
SPECIALISTS
pty LTD

Fasteners for Roofing, Cladding
and General Construction

Product Group 11

Filler Blocks

Description

Profile Fillers supplied in Polyethylene but also available in EPDM and High Density Metalocene polyolefin, vented if necessary

Typical Application

Profiled foam fillers are designed to seal roofing and cladding profiles against dust, water and water vapor ingress.



Product Features

Fillers are supplied:

- Made-to-measure
- In a range of materials, thicknesses & colors
- Vented (tops off or nicks to base)
- Angle-cuts

Typical Applications

- Sealing eaves
- Sealing ridges
- Sealing roof lights

MAK Fastener Specialists Pty Ltd.,
 Unit 4, 11 Trevi Crescent,
 Tullamarine, VIC 3043
 Australia.

Web Site: www.makfasteners.com.au

Tel.: +61 (0)3 9078 9119

Fax: +61 (0)3 9078 9119

E-mail: Sales@MakFasteners.com.au



MAK
FASTENER
SPECIALISTS
 pty LTD

Fasteners for Roofing, Cladding
 and General Construction

Product Group 11 *Filler Blocks*

Technical Information

	J25	J30	J50
Type	Standard	Standard	Standard
Material	Fully closed cell cross-linked PE	Fully closed cell cross-linked PE	Fully closed cell cross-linked PE
Colour	Black, white or black and white mixed	Black, white	Black, white
Thickness	25mm	30mm	50mm
Density (kg/m ³)	33	33	33
Service temp. (C)	-70°C to +95°C	-70°C to +95°C	-70°C to +95°C
Durability	20 years	20 years	20 years